

Thermal H10 Bath fluid

JULABO *Thermal* bath fluids are ideally suited for all of your temperature control applications and guarantee safe and reliable operation. Choosing the proper bath fluid is critical for best results in temperature control. Viscosity, oxidation characteristics and heat transfer of Thermal fluids are specifically matched with each JULABO temperature control unit. JULABO Thermal bath fluids have been carefully selected and are optimized for maximum performance with JULABO instruments.



Benefits

- Low toxicity
- Low viscosity
- High stability
- Minimum odor
- Good heat conductivity
- Low corrosion tendency
- Wide temperature ranges

Technical Data

Order no. 5 liters	8940115
Order no. 10 liters	8940114
Working temperature (°C)	-20...+180
Flash point (°C)	190
Fire point (°C)	216
Viscosity (kinematic at 20 °C in mm ² /s)	10.8
Density (at 20 °C in g/cm ³)	0.94
Pour point (°C)	-90
Boiling point (°C)	>300
Ignition temperature (°C)	>400
Color	clear

JULABO Contact

JULABO GmbH
Eisenbahnstr. 45
77960 Seelbach / Germany

Tel. +49 (0) 7823 51-0
info.de@julabo.com

JULABO Services

Product finder, Accessory search, 1 PLUS Warranty, Catalog download, Callback service, Operating manuals, Safety data sheets, Software and more

www.julabo.com