# LAB & INDUSTRY EQUIPMENT

# **BUCH & HOLM**



#### Buch & Holm A/S



## Introducing the 63 Series

The 63 series range includes models 6300 and 6320D which cover the visible region of the spectrum and model 6305 which uses a pulsed xenon lamp to extend the wavelength range into the UV region of the spectrum. All three models have measurement modes for absorbance, % transmittance and concentration. This makes them ideal for basic photometrics applications in schools and colleges, as well as in quality control laboratories.

#### **Key Features**

- Multi-parameter display with wavelength and photometric readouts
- Small footprint
- Wide range of sampling accessories
- Domed lid of 6320D accepts tubes up to 105mm
- 6305 utilises a high quality pulsed xenon lamp
- Easy and intuitive operation
- 3 year warranty



#### Versatile and Flexible Accessories

The 63 series has been specifically designed to enable a wide range of accessories to be easily fitted and used. To accommodate various sample volumes there are a wide range of passive accessories available including an adjustable cuvette holder which can hold cuvettes between 10 and 100mm (part code 630 005); a test tube holder for test tubes with diameters between 16 and 24mm (part code 637 071); and for small sample volumes there is a micro-cuvette holder with a reduced aperture (part code 630 304). For multiple samples Jenway offer a four position rotary cuvette holder (part code 634 001).

#### Temperature Control

Where temperature control is important Jenway offer a water heated cuvette option (part code 648 001) which requires a water bath and circulator (not supplied). For sampling applications Jenway offer an external sipper pump system (part code 632 001) which can be programmed to deliver

controlled and reproducible sample volumes into the chamber of a flow-through cuvette along with air and segmentation rinse cycles.



4 cell turret

Part code: 634 001



### Design

The 63 series spectrophotometers are small and lightweight, making them easy to store or move to different locations within the laboratory. These instruments are easy to navigate, using push buttons to move round the simple user interface.

The design of model 6320D is based on the successful 6300 platform. It has been designed with a domed lid which enables test tubes, up to a height of 105mm, to be used. Model 6320D is supplied fitted with a dual cell holder (part code 632 511) so that either test tubes or standard 10x10mm cuvettes can be used to measure samples. All three models are covered by a 3 year warranty.



## 63 Series Accessories Ordering Information

| Part Code | Description   |                    |
|-----------|---|--------------------|
| 630 204   | 10x10mm path length cuvette holder  |                    |
| 630 005   | 10 to 100mm path length cuvette holder  |                    |
| 634 001   | 4 position manual cuvette holder  |                    |
| 630 304   | Micro-cuvette holder with reduced aperture  |                    |
| 632 511   | Dual cell holder for 10mm cuvettes and 12.7mm diameter  |                    |
|           | tubes (for use with 6320D only)   | •                  |
| 637 071   | 10mm square cuvette and 16, 24mm test tube holder   |                    |
| 632 001   | Sipper Pump supplied with inlet and outlet tubing (230V/50Hz)                                 |                    |
| 632 031   | Sipper Pump supplied with inlet and outlet tubing (110V/60Hz)                                 | 6320D Cell holder  |
| 648 001   | Water heated single cuvette holder  | Part code: 632 511 |
| 012 094   | Xenon lamp module (6305)  |                    |
| 012 075   | Tungsten halogen lamp (6300/6320D)  |                    |
| 543 001   | 40 column serial printer supplied with interface cable, paper roll and universal power supply |                    |



# Ordering Information

| Product Code       | Description   |
|--------------------|---|
| 630 501            | 6300 visible spectrophotometer supplied with mains lead, pack 100 disposable cuvettes, 10 x 10mm cell holder, interface cable and PC application software on CD-ROM* (230V/50Hz)    |
| 630 531            | 6300 visible spectrophotometer supplied with mains lead, pack 100 disposable cuvettes, 10 x 10mm cell holder, interface cable and PC application software on CD-ROM* (110V/60Hz)    |
| 632 501            | 6320D visible spectrophotometer supplied with mains lead and dual cell holder (for 10mm square cuvettes and 12.7mm diameter tubes) (230V/50Hz)                                      |
| 632 521            | 6320D visible spectrophotometer supplied with mains lead and dual cell holder (for 10mm square cuvettes and 12.7mm diameter tubes) (110V/60Hz)                                      |
| 635 001            | 6305 UV/visible spectrophotometer supplied with mains lead, pack 100 disposable cuvettes, 10 x 10mm cell holder, interface cable and PC application software on CD-ROM* (230V/50Hz) |
| 635 031            | 6305 UV/visible spectrophotometer supplied with mains lead, pack 100 disposable cuvettes, 10 x 10mm cell holder, interface cable and PC application software on CD-ROM* (110V/60Hz) |
| * requires free or | n-line registration   |

# **Technical Specification**

| Parameter                | 6300 and 6320D              | 6305                        |
|--------------------------|-----------------------------|-----------------------------|
| Wavelength range         | 320 to 1000nm               | 198 to 1000nm               |
| Wavelength resolution    | 1nm                         | 1nm                         |
| Wavelength accuracy      | ±2nm                        | ±2nm                        |
| Spectral bandwidth       | 8nm                         | 8nm, 6nm over UV range      |
| Transmittance            | 0 to 199.9%T                | 0 to 199.9%T                |
| Absorbance               | -0.300 to 1.999A            | –0.300 to 1.999A            |
| Accuracy                 | ±1%T                        | ±1%T                        |
| Resolution               | 0.1%T, 0.001A               | 0.1%T, 0.001A               |
| Stray light              | <0.5%T                      | <0.5%T at 220 and 340nm     |
| Noise                    | <1%                         | <0.001A at 0A at 400nm      |
| Stability                | 1%/h after 15 minutes       | <0.002A/h after 30 minutes  |
| Concentration range      | –300 to 1999                | –300 to 1999                |
| Concentration resolution | 0.1 to 1                    | 0.1 to 1                    |
| Units                    | ppm, mg/l, g/l, M, %, blank | ppm, mg/l, g/l, M, %, blank |
| Factor                   | 0 to 999.9, 1000 to 9999    | 0 to 999.9, 1000 to 9999    |
| Light source             | Tungsten halogen lamp       | Xenon lamp                  |
| Outputs                  | Analogue and RS232          | Analogue and RS232          |
| Power                    | <50W                        | <50W                        |
| Size (w x d x h)         | 365 x 272 x 160mm           | 365 x 272 x 160mm           |
| Weight                   | 6kg                         | 6kg                         |



Bibby Scientific - UK (Group HQ) Beacon Road, Stone, Staffordshire, ST15 OSA, United Kingdom

Tel: +44 (0)1785 812121 Fax: +44 (0)1785 813748 e-mail: sales@bibby-scientific.com sales@bibby-scientific.com

www.jenway.com



Find out more!!!

Please scan the QR/Mobile Tag with your smartphone for more information