

EN 12390-2

Vibrating Tables

Ⓐ Electrical Vibrating Table

- with foot switch, incl. 2.5 m cable and plug
 - electrogalvanized version
 - table plate with 2 diagonally arranged upstands
 - table size: 310 x 310 mm
 - vibrations/rotations: 3000 U/min
 - height: 170 mm
 - weight approx.: 19 kg
 - electrical connection: 230 V / 50 Hz
- Order-No. B17134

Ⓑ Electrical Vibrating Table

- with foot switch, incl. 2.5 m cable and plug
 - electrogalvanized version
 - table plate with 2 diagonally arranged upstands
 - table size: 310 x 310 mm
 - vibrations/rotations: 3000 U/min
 - height: 170 mm
 - weight approx.: 17.5 kg
 - connection to 12 V vehicle electrical system
fuse protection min. 15 A
- Order-No. B17135

Ⓒ Electrical Vibrating Table

- with foot switch, incl. 2.5 m cable and plug
 - electrogalvanized version
 - table plate with 2 diagonally arranged upstands
 - table size: 400 x 400 mm
 - vibrations/rotations: 3000 U/min
 - height: 170 mm
 - weight approx.: 18 kg
 - electrical connection: 230 V / 50 Hz
- Order-No. B1714

Ⓓ Electrical Vibrating Table

- with foot switch, incl. 2.5 m cable and plug
 - electrogalvanized version
 - table plate with 2 diagonally arranged upstands
 - table size: 500 x 500 mm
 - vibrations/rotations: 3000 U/min
 - height: 170 mm
 - weight approx.: 20 kg
 - electrical connection: 230 V / 50 Hz
- Order-No. B17141

Ⓔ Electrical Vibrating Table

- especially for beam moulds
 - with integrated foot switch
 - incl. 2.5 m cable and plug
 - electrogalvanized version
 - table plate with upstands
(left and right as well as at the front and the back)
 - table size: 380 x 780 mm
 - with 2 motors
 - vibrations/rotations: 3000 U/min
 - height: 200 mm
 - weight approx.: 17.5 kg
 - electrical connection: 230 V / 50 Hz
- Order-No. B17202



Vibrating Tables

High-Frequency Vibrating Table

- with time switch, range 0 - 120 sec.
- incl. 2.5 m cable and plug
- galvanized version
- table plate with 2 diagonally arranged upstands
- table size: 330 x 550 mm
- vibrations/rotations: 9000 U/min
- height: 270 mm
- weight approx.: 34 kg

A • permanent operation switch
• electric supply: 230 V / 50 Hz
Order-No. B17182

B • with speed control
• electric supply: 230 V / 50 Hz - 0.75 kW
Order-No. B171824

ⓐ Magnet-Vibrating Table - Stationary Version


- 1 clamping magnet field with optimal alignment for one steel mould 150 x 150 mm
 - with external control panel
 - control panel with integrated display of speed control and preset time. Speed control is possible from 2000 to 6000 rpm.
 - electronic time switch
 - electrogalvanized
 - dimensions (LxWxH): 360 x 400 x 208 mm
 - working surface: approx. 370 x 330 mm
 - weight approx.: 46 kg
 - electric supply: 230 V / 50 Hz
- Order-No. B17220

ⓑ Magnet-Vibrating Table - Mobile Version

available as alternative

ⓒ Internal Vibrator

- consisting of:
- drive motor: 230 V / 50 Hz
 - vibrations: 18,000 U/min.
 - power input: 2800 Watt
 - vibrator: Ø 25 mm
 - hose length: 3.0 m
 - weight approx.: 13.5 kg
 - with carrying strap
- Order-No. B180142



FORM+TEST Seidner & Co. GmbH

Zwiefalter Str. 20 • D-88499 Riedlingen

phone: +49 (0) 7371 9302-20 • fax: -99

www.formtest.de

sales@formtest.de