


P-14

ROTOR MILL

TECHNICAL SPECIFICATIONS





Contents

Technical data.....	page 3
Accessories.....	page 6
Application examples	page 14



Technical data

P-14 – ROTOR MILL

Fields of applications	fine grinding
Industry & areas of application	food & feed, agriculture, plastics and textiles, chemistry, environment & recycling, medicine & pharmaceuticals, biology, metallurgy
Material properties, feed materials	soft, medium-hard, brittle, tough, elastic, fibrous, temperature-sensitive
Grinding principle	impact, shearing, cutting
Feed size¹⁾	< 15 mm
Final fineness¹⁾	< 40 µm
Batch/feed quantity²⁾	470 ml/ 600 ml ¹⁾ 60 l/20 l/5000 ml/2000 ml/1000 ml/500 ml/ 250 ml with cyclone
Rotational speed at 50 Hz (60Hz)	2000 – 24000 min ⁻¹ ; impact rotor 2000 – 18000 min ⁻¹ ; cutting rotor
Peripheral speed	
impact rotor	10.2 m/s – 121.9 m/s
cutting rotor	8.8 m/s – 79.2 m/s
Rotor diameter	97 mm impact rotor 84 mm cutting rotor
Rotor types	6-12-24 rib rotor cutting rotor 3 blades
Material of the grinding tools	stainless steel, stainless 316 L, pure titanium grade 2, cutting rotor hardened stainless steel with tungsten carbide; TiN coated + zirconium blades and titan

¹⁾ depending on material and sieve selection

²⁾ per bulk density & bulk volume standard pan

Sieve size	trapezoidal perforation ³⁾ 0.08/0.12/0.2/0.5/0.75/1.0/1.5/2.0 mm
	round perforation ³⁾ 1.0/2.0/4.0/6.0 mm
	square perforation ³⁾ 2.0/4.0/6.0 mm
	trapezoidal perforation ⁴⁾ 0.08/0.12/0.2/0.5/0.75/1.0/2.0 mm
	square perforation ⁴⁾ 2.0/4.0/6.0 mm
	round perforation ⁴⁾ 1.0/1.5/2.0/3.0/4.0 mm
Engine mounting	ceramic hybrid bearing
SOP management	yes; 20 SOP's with plain text declaration
Multilingual menu navigation	yes, 7 languages: English, Italian, Spanish, French, Chinese, Arabic, German
Possibility of remote control via USB-interface	yes
Graphical display trend display of temperature/speed power consumption/rotational speed	yes, variable sampling rates can be set
Detection and visualisation in the user interface of the labyrinth disk, collection vessel and lid collection vessel	yes
Error memory with real-time display	yes, display of the error message in plain text format
Integrated energy measurement to record the grinding energy	yes
Setting grinding time	yes
Power-dependent infinitely variable feed control via vibrating channel	yes
Control options of cyclone or vacuum cleaner via user interface	yes
Drive	3-phase current asynchronous motor with frequency converter
Power supply	200 -240 V/~ 1 (50 – 60 Hz)



Protection class	IP 22
Power consumption	2700 VA (200..240 V)
Drive power	2500 Watt
W x H x D	420 x 520 x 450 mm
Weight	33 kg (net)
Norm standards	CE, UKCA, UL/CSA



Accessories

P-14 – ROTOR MILL

order no.

article

Instrument without grinding parts, incl. funnel and funnel lid

14.8020.00 for 200-240 V/1~, 50-60 Hz, 2700 watts

Other voltages on request!



Collecting vessel with lid and labyrinth disk, impact resp. cutting rotor, as well as sieve ring resp. sieve shells are additionally necessary!

Accessories for use as Rotor Mill

Accessories for standard applications with the impact rotor and sieve rings

14.6315.00 collecting vessel with outlet and lid made of stainless steel 316L and labyrinth disk made of aluminium for connecting to FRITSCH cyclone separators

NEW

14.6310.00 collecting vessel with lid made of stainless steel 316L and labyrinth disk made of aluminium

NEW

Impact rotors with cooling fins made of stainless steel

14.4330.10 with 6 ribs

14.4334.10 with 12 ribs

14.4337.10 with 24 ribs

Sieve rings with reinforced edges made of stainless steel 316L

14.4341.00 0.08 mm trapezoidal perforation

14.4342.00 0.12 mm trapezoidal perforation

14.4343.00 0.2 mm trapezoidal perforation

14.4344.00 0.5 mm trapezoidal perforation

14.4345.00 0.75 mm trapezoidal perforation



order no.	article
14.4346.00	1 mm trapezoidal perforation
14.4347.00	1.5 mm trapezoidal perforation
14.4348.00	2 mm trapezoidal perforation
14.4355.00	2 mm square perforation
14.4357.00	4 mm square perforation
14.4359.00	6 mm square perforation
14.4360.00	1 mm round perforation
14.4361.00	2 mm round perforation
14.4362.00	4 mm round perforation
14.4363.00	6 mm round perforation

Accessories for grinding in the analytical sector, for food and pharmaceutical industry and for sample preparation with special focus on increased resistance to corrosion, alkalis and acids

14.6385.00	collecting vessel with outlet and lid and labyrinth disk made of stainless steel 316L for connecting to FRITSCH cyclone separators
14.6380.00	collecting vessel with lid and labyrinth disk made of stainless steel 316L
14.4335.10	impact rotor with 12 ribs and cooling fins made of stainless steel 316L



Please note: sieve ring with reinforced edges made of stainless steel 316L is additionally necessary!

Accessories for heavy-metal- and iron-free grinding and sample preparation according to RoHS

14.6415.00	collecting vessel with outlet PTFE-coated and lid made of pure titanium and labyrinth disk made of aluminium for connecting to small volume cyclone separator
14.6410.00	collecting vessel PTFE-coated with lid made of pure titanium and labyrinth disk made of aluminium

order no. article

Impact rotors with cooling fins made of pure titanium

14.4430.32 with 6 ribs

14.4434.32 with 12 ribs

14.4437.32 with 24 ribs

Sieve rings with reinforced edge made of pure titanium

14.4441.32 0.08 mm trapezoidal perforation

14.4442.32 0.12 mm trapezoidal perforation

14.4443.32 0.2 mm trapezoidal perforation

14.4444.32 0.5 mm trapezoidal perforation

14.4445.32 0.75 mm trapezoidal perforation

14.4446.32 1 mm trapezoidal perforation

14.4447.32 1.5 mm trapezoidal perforation

14.4448.32 2 mm trapezoidal perforation

Accessories for difficult-to-mill and temperature-sensitive samples

14.6315.00 collecting vessel with outlet and lid made of stainless steel 316L and labyrinth disk made of aluminum for connecting to FRITSCH cyclone separators

NEW

14.6310.00 collecting vessel with lid made of stainless steel 316L and labyrinth disk made of aluminum

NEW

14.4470.00 impact bar

Impact rotors with cooling fins made of stainless steel

14.4330.10 with 6 ribs

14.4334.10 with 12 ribs

14.4337.10 with 24 ribs

Sieve rings for impact bar made of stainless steel 316L

14.4481.10 0.08 mm trapezoidal perforation

14.4482.10 0.12 mm trapezoidal perforation

14.4483.10 0.2 mm trapezoidal perforation



order no.	article
14.4496.10	0.35 mm trapezoidal perforation
NEW	
14.4484.10	0.5 mm trapezoidal perforation
14.4485.10	0.75 mm trapezoidal perforation
14.4486.10	1 mm trapezoidal perforation
14.4487.10	1.5 mm trapezoidal perforation
14.4488.10	2 mm trapezoidal perforation
14.4497.10	2 mm square perforation
14.4498.10	4 mm square perforation
14.4499.10	6 mm square perforation
14.4490.10	1 mm round perforation
14.4491.10	2 mm round perforation
14.4492.10	4 mm round perforation
14.4493.10	6 mm round perforation

Sieve rings are also available in further perforations.

order no. article

Accessories for use as Cutting Mill

Accessories for standard applications with the cutting rotor and sieve shells

14.6515.00 collecting vessel with outlet and lid made of stainless steel and labyrinth disk made of aluminium for connecting to FRITSCH cyclone separators

14.6510.00 collecting vessel with lid made of stainless steel and labyrinth disk made of aluminium

14.6590.00 cutting rotor made of stainless steel consisting of cutting rotor with cooling fins and sieve shells holder made of stainless steel and rotor edges and fixed knives made of hardened stainless steel

NEW

14.4540.00 sieve shells holder without cutting rotor with fixed knives made of hardened stainless steel

14.6595.00 cutting rotor made of hardmetal tungsten carbide consisting of cutting rotor with cooling fins and sieve shells holder made of stainless steel and rotor edges and fixed knives made of hardmetal tungsten carbide

NEW

14.4585.00 sieve shells holder without cutting rotor with fixed knives made of hardmetal tungsten carbide

Sieve shells made of stainless steel 316L

14.4541.00 0.08 mm trapezoidal perforation

14.4542.00 0.12 mm trapezoidal perforation

14.4543.00 0.2 mm trapezoidal perforation

14.4544.00 0.5 mm trapezoidal perforation

14.4545.00 0.75 mm trapezoidal perforation

14.4546.00 1 mm trapezoidal perforation

14.4547.00 1.5 mm trapezoidal perforation

14.4548.00 2 mm trapezoidal perforation

14.4552.00 2 mm square perforation

14.4554.00 4 mm square perforation



order no.	article
14.4556.00	6 mm square perforation
14.4560.00	1 mm round perforation
14.4561.00	1.5 mm round perforation
14.4562.00	2 mm round perforation
14.4563.00	3 mm round perforation
14.4564.00	4 mm round perforation

Accessories for heavy-metal- and iron-free grinding and sample preparation according to RoHS

14.4615.00	collecting vessel with outlet PTFE-coated and lid made of pure titanium and labyrinth disk made of aluminium for connecting to small volume cyclone separator
------------	---

14.4610.00	collecting vessel PTFE-coated with lid made of pure titanium and labyrinth disk made of aluminium
------------	---

NEW	14.4690.00	cutting rotor TiN-coated with knives made of pure titanium consisting of cutting rotor with cooling fins and sieve shells holder made of stainless steel TiN-coated, rotor edges and fixed knives made of pure titanium
------------	------------	---

NEW	14.4695.00	cutting rotor TiN-coated made of zirconium oxide consisting of cutting rotor with cooling fins and sieve shells holder made of stainless steel TiN-coated, rotor edges and fixed knives made of zirconium oxide
------------	------------	---

Sieve shells, TiN-coated

14.4644.00	0.5 mm trapezoidal perforation
------------	--------------------------------

14.4646.00	1 mm trapezoidal perforation
------------	------------------------------

14.4648.00	2 mm trapezoidal perforation
------------	------------------------------

Sieve shells are also available in further perforations.

N° de commande Désignation

Sample exhaustion with cyclone separators and for grinding large quantities

High-performance cyclone separator

14.4807.00 high-performance cyclone separator made of stainless steel 316L, incl. sample glass 1 liter

NEW

Collecting vessels for high-performance cyclone separator

83.3250.00 sample glass 1 liter

83.3260.00 sample glass 2 liters

83.3270.00 sample glass 5 liters

45.8040.00 collecting vessel, 20 liters made of stainless steel 316L

45.8050.00 collecting vessel, 60 liters made of stainless steel 316L

Small volume cyclone separator

14.8140.00 small volume cyclone separator made of plastic, incl. sample glass 500 ml

NEW

45.8218.16 replacement fine-dust filter 80-100 µm for small volume cyclone separator for passive utilization

45.8219.16 replacement fine-dust filter 35-40 µm for small volume cyclone separator for passive utilization

Collecting vessels for small volume cyclone separator

27.1450.00 sample glass 250 ml

27.1460.00 sample glass 500 ml

Exhaust system for high-performance and small volume cyclone separator and for cooling the P-14

86.5505.00 switch box for controlling the exhaust system directly via the Rotor Mill P-14 for 100–240 V/1~, 50 – 60 Hz, up to 3600 watts



N° de commande	Désignation
14.8128.00	connecting piece for exhaust system (for additional cooling of the P-14)

NEW

43.9070.00	exhaust system, dust category „M“ according to DIN EN 60335-2-69 for 230 V/1~, 50/60 Hz, 1,600 watts
43.9055.00	fleece filter bag for exhaust system (pack = 5 pieces) ⁵⁾
43.9052.00	plastic bag for exhaust system (pack = 5 pieces) ⁵⁾

Certification

96.0450.00	IQ/OQ documentation (questionnaire format - implementation not included)
------------	--

NEW

Accessories for automatic sample feeding

Sample Feeder L-24

Instrument incl. V-shaped channel, funnel and control unit

24.0030.00	for 200-240 V/1~, 50-60 Hz, 25 watts
24.0040.00	for 100-120 V/1~, 50-60 Hz, 25 watts
14.8130.00	L-24 mount for P-14, incl. connection cable for automatic control of the L-24 via the Rotor Mill P-14

NEW


Certification

96.0370.00	IQ/OQ documentation (questionnaire format – implementation not included)
------------	--

⁵⁾ Remark: One pack/one piece is included in the scope of delivery of the exhaust system.

Application examples

ROTOR MILL AND CUTTING MILL



Sample:
epoxy resin

Accessories:
cyclone
impact rotor with 12 ribs
0.2 mm trapezoidal perforation



Sample:
pellet food for rabbits

Accessories:
impact rotor with 12 ribs
0.5 mm trapezoidal perforation



Sample:
wood chips

Accessories:
cutting rotor
2 mm trapezoidal perforation



Sample:
juniper

Accessories:
impact rotor with 12 ribs
0.75 mm trapezoidal perforation



Contact us now
for a non-binding
consultation or
individual test grinding
to identify your ideal
device configuration
and optimal grinding
parameters.



